LED FLEX BATTERY WORK LIGHT

Article number: 111550



LED Flex Battery 2000, dimmable construction spotlight. Compatible with 18V batteries from power tool manufacturers Bosch and Makitasimply insert your existing battery and start using it; a compatible battery adapter is included. High-output LED spotlight with three dimming levels: 2000 / 1050 / 550 lumens, plus an additional SOS warning function. Battery (not included) protected against deep discharge. Flexible use via stand, hanging, or tripod mounting. Robust and stable metal housing, rotates 360°, tilt angle continuously adjustable. Light color: daylight white (approx. 5700 K), color rendering Ra 82. Operating time depends on battery and dimming level. Dimensions: L 235 x W 225 x H 260 mm.

Length (mm)	245 mm
Width (mm)	233 mm
Height (mm)	270 mm
Weight (kg)	1,7 kg

Attribute	Value
Long	245 mm
Power supply	Akku
Protection class (IP)	IP54
width	233 mm
Diameter	- mm
Cable length	- m
Light source	LED nicht austauschbar
With illuminant	Yes
Suitable for number of light sources	1
rated voltage	14.4 V - 18 V
With switch	Yes
Surrounding product according to 2019/2020/EU	No
Protection class according to IEC 61140	III
Rated luminous flux according to IEC 62722-2-1	2000 lm - 2000 lm
light color	wei
color temperature	5700 K - 5700 K
Color rendering index CRI	80-89
With suspension hook	No
With connecting cable and plug	No

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

With bracket	No
With charging station	No
Height/Depth	270 mm
Maximum system performance	18 W
Operating time with battery pack	- h

GTIN: 4021103092859

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.