LED PRO 1500 WORK LIGHT

Article number: 111572

LED Pro 1500, dimmable construction spotlight. Compact dimensions: 128 x 45 x 100 mm. 2K housing, IP54 rating for protection against dust and splashing water, impact resistance rating IK07. Five dimming levels: 1500-300 lm. Housing rotates 360° for optimal illumination. Strong holding magnets and tripod thread for universal mounting. Operating time up to 17 hours. LED indicator for brightness level and battery charge status. USB output (power bank function). Rechargeable, USB-C charging cable included.



Length (mm)	155 mm
Width (mm)	50 mm
Height (mm)	120 mm
Weight (kg)	0,54 kg

Attribute	Value
Long	155 mm
Power supply	Akku
Protection class (IP)	IP54
width	50 mm
Diameter	- mm
Cable length	- m
Automatic cable rewind	No
Light source	LED nicht austauschbar
With illuminant	Yes
Suitable for number of light sources	1
rated voltage	37 V - 37 V
With switch	Yes
Surrounding product according to 2019/2020/EU	No
Protection class according to IEC 61140	III
Rated luminous flux according to IEC 62722-2-1	300 lm - 1500 lm
light color	wei
color temperature	6500 K - 6500 K
Color rendering index CRI	80-89
With suspension hook	No
With connecting cable and plug	No
With bracket	No
With charging station	No
Height/Depth	120 mm

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.

Maximum system performance	- W
Operating time with battery pack	- h

GTIN: 4021103092033

CIMCO Werkzeuge GmbH & Co. KG
Hohenhagener Straße 1 – 5
42855 Remscheid
Telefon +49 2191 3718-01
info@cimco.de • cimco.de

The technical data are empirical values according to the current state of production and are subject to customary tolerances, but do not represent guaranteed properties. We reserve the right to make technical changes.